



Standard Accessories:

- Drill Chuck and Arbor
- Spindle Guard
- Lamp
- Reducing Sleeves
- Drill Drifts
- Tool Box
- Manual and Parts List

Model	GB25
Drilling Capacity (Mild Steel)	25mm
Drilling Capacity (Cast Iron)	28mm
Tapping Capacity (Mild Steel)	18mm
Tapping Capacity (Cast Iron)	22mm
Distance from Spindle to Column	250mm
Distance from Spindle to Table (min/max)	825mm
Distance from Spindle to Base (min/max)	1220mm
Vertical Travel of Table	700mm
Column Diameter	98mm
Number of Spindle Speeds	12
Range of Spindle Speeds	75-3200rpm
Spindle Taper	MT3
Table Size	380 x 380mm
Number and size of T slots on Base/Table	2, 14
Maximum Spindle Traverse (hand/power)	100mm
Base Size Overall	535 x 360mm
Base Working Surface	300 x 265mm
Main Motor Power (2 speed motor)	1.1/0.8kW (1.48/1.14hp)
Power Supply	240v or 415v
Net Weight	200kg
Machine Dimensions	600 x 400 x 1700mm

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.