



Features:

- Hydraulic drive for smooth, consistent blade action
- Heavy welded steel body, blade frame, and worktable
- Adjustable blade clearance to suit material thickness
- Auto and inch operating modes via foot pedal



CHES-4x2030



**HES-3.5x3050/
HES-4.5x2000**



HES-6.5x1300

Model	CHES-4x2030	HES-3.5x3050	HES-4.5x2000	HES-6.5x1300
Max. Shearing Thickness	4mm	3.5mm	4.5mm	6.5mm
Max. Shearing Width	2032mm	3050mm	2000mm	1300mm
Back Gauge	650mm	920mm (electric)	630mm (manual)	630mm (electric)
Front Gauge	600mm	700mm	700mm	700mm
Shearing Angle	1°40'	1°40'	2°	2.5°
No. of Stroke (Per Minute)	15/min	14/min	18/min	20/min
Motor Power	4kW (5.36hp)	5.5kW (7.38hp)	7.5kW (10.05hp)	5.5kW (7.38hp)
Dimensions	2600 x 1150 x 1500mm	4000 x 3000 x 1800mm	2700 x 3000 x 1700mm	2000 x 2700 x 1700mm
Net Weight	1700kg	5200kg	2900kg	2470kg

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.