



Features:

- Robust Steel Frame Construction
- Moveable Hydraulic Cylinder
- User Friendly Maintenance

Standard Accessories:

- Safety Fence
- V Block
- Dedicated Lifting Sling

Model	WP50H	WP80H	WP100H	WP150H	WP200H	WP300H
Maximum Force	51T	82T	102T	153T	204T	306T
Hydraulic Pressure	30Mpa	30Mpa	30Mpa	30Mpa	30Mpa	28.5Mpa
Cylinder Stroke	250mm	250mm	300mm	300mm	300mm	300mm
Ram Speed (Forward/Return)	4/5mm/s	4.6/6.1mm/s	7.6/10.5mm/s	4.9/6.7mm/s	3.9/5.8mm/s	5.9/8.5mm/s
Worktable (Size/Inner hole Diameter)	550x350mm/ Φ 120mm	650x415mm/ Φ 120mm	650x440 mm/ Φ 120mm	700x530mm/ Φ 120mm	750x550mm/ Φ 150mm	800x685mm/ Φ 150mm
Worktable Travel (Increments x Distance)	4 x 150mm	3 x 250mm	5 x 150mm	5 x 150mm	5 x 150mm	2 x 300mm
Motor Power	2.2kW (3.0HP)	4kW (5.4HP)	7.5kW (10.1HP)	7.5kW (10.1HP)	7.5kW (10.1HP)	22kW (29.5HP)
A	1026mm	1490mm	1480mm	1476mm	1686mm	1626mm
B	700mm	950mm	790mm	870mm	900mm	1020mm
C	1825mm	2067mm	2042mm	2215mm	2310mm	2345mm
D	700mm	1050mm	1100mm	1100mm	1300mm	1300mm
E	1010mm	962mm	808mm	890mm	864mm	764mm
I	325mm	469mm	597mm	599mm	669mm	748mm
J	320mm	580mm	640mm	580mm	730mm	610mm
Weight	860kg	1205kg	1430kg	2220kg	2830kg	3950kg

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.