



Inside our Compact Turn 21

Model	Compact Turn 21
Max. Swing Over Bed	210mm
Distance between Centers	400mm
Rail Width	100mm
Spindle Bore Dia.	26mm
Spindle Taper	MT4
Spindle Speed	3000rpm
Tool Post	4-position
X- axis Travel	90mm
Z- axis Travel	300mm
X Rapid Speed	2000mm/min
Z Rapid Speed	2000mm/min
Spindle Motor Power	1.2kw
Main Motor Type	Servo Motor
Controller System	Siemens 808D
X Motor Torque	1.9N.M
Z Motor Torque	1.9N.M
Min. Setting Unit	0.001mm
Tailstock Dia.	22mm
Tailstock Travel	50mm
Tailstock Taper	MT2
Packing size (without stand)	1170 x 700 x 860mm
Overall Size	1300 x 800 x 1500mm
Net Weight (without stand)	200kg
Net Weight	230kg

Standard Accessories:

- Siemens 808D Control
- 3 Jaw Chuck Manual Type
- Electric 4 Station Tool Post
- Machine Stand
- LED Work Lamp
- Coolant System
- Electric Handwheel
- Full Cover with CE Safety Clock
- Auto Lubrication
- Cutting Tools
- 4 Jaw Chuck
- Soft Jaw

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.